



Long Tire Life

Deep lugs, low slip and optimized rubber compounds help reduce wear to give exceptionally long tire life. In addition, a sharp vertical lug design allows the Agribib to retain traction even when 70% worn.

Exceptional Traction: Year Round

Strong but super-flexible sidewalls allow a long footprint, putting more lugs in direct contact with the soil. Michelin's exclusive "self-cleaning hinge" between the lugs ensures that the tread stays free of mud for maximum pulling power in wet conditions.

Low Soil Compaction - Excellent Flotation

A super-flat tread spreads the load evenly across a generous footprint, helping to reduce the tire's penetration into soft soil. Low slip and ultra-low working pressures help reduce soil compaction and damage.

Exceptional Comfort

The swept-back 45 degree lug design delivers a surprisingly smooth ride on the road. Uniform "round" construction plus Michelin's super-strong but ultra-flexible casing deliver exceptional ride and comfort, in the field and on the road.

English Units

Agribib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
11.2R24 TL 114A8/111B 2 Star		70146	43.0	19.6	129.6	131	47	3,894	27
12.4R24 TL 119A8/116B 2 Star		78449	45.2	20.5	134.6	155	52	4,488	27
13.6R24 TL 121A8/118B 2 Star		97644	47.1	21.2	140.1	168	54	4,796	27
14.9R24 TL 126A8/123B 2 Star		75971	49.6	22.1	147.0	212	60	5,610	27
16.9R24 TL 134A8/131B 2 Star		97341	52.4	23.1	154.9	244	69	6,996	27
12.4R28 TL 121A8/118B 2 Star		50465	49.7	22.7	148.2	161	50	4,796	27

Agribib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
13.6R28 TL 123A8/120B 2 Star	340/85R28	87976	51.5	23.3	153.3	192	58	5,126	27
14.9R28 TL 128A8/125B 2 Star	380/85R28	47219	53.5	24.1	159.4	235	59	5,940	27
16.9R28 TL 136A8/133B 2 Star	420/85R28	86531	56.2	25.2	166.9	262	64	7,392	27
380/85R30 135A8/135B TL	14.9R30	18784	55.7	24.7	165.1	0	58	6,160	23
420/90R30 TL 147A8/147B	16.9R30	68713	60.4	27.2	179.4	263	55	10,175	41
16.9R30 TL 137A8/134B 2 Star	420/90R30	41545	58.3	26.1	173.0	279	62	7,590	27
18.4R30 TL 142A8/139B 2 Star		42060	61.0	27.4	181.2	328	68	8,756	27
320/85R34 TL 133A8/130B	12.4R34	73532	55.9	25.6	167.1	169	49	6,765	41
380/85R34 TL 137A8/137B	14.9R34	59412	59.2	26.5	175.6	251	52	7,590	27
420/85R34 142A8/142B TL Agribib	16.9R34	84230	62.2	27.8	184.6	299	64	8,360	26
16.9R34 TL 139A8/136B 2 Star	420/85R34	54573	62.4	28.2	185.7	289	64	8,030	27
18.4R34 TL 144A8/141B 2 Star		40989	65.4	29.3	194.2	315	68	9,240	27
12.4R38 TL 125A8/122B 2 Star		50333	59.1	27.2	176.4	182	44	5,456	27
13.6R38 TL 128A8/125B 2 Star		66666	61.6	28.4	185.2	187	57	5,940	27
380/80R38 142A8/142B TL Agribib	14.9R38	30231	62.1	28.4	186.1	0	58	8,800	41
420/85R38 144A8/144B TL Agribib	16.9R38	84239	66.0	29.5	195.9	319	64	9,240	27
16.9R38 TL 141A8/138B 2 Star		42119	66.3	29.9	197.1	306	64	8,492	27

Agribib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
18.4R38 TL 146A8/143B 2 Star	480/80R38	72676	69.7	31.3	207.0	356	68	9,900	27
520/85R38 TL 155A8/155B	20.8R38	43308	73.0	32.3	217.7	443	64	12,760	27
480/80R42 (18.4R42) 156A8/156B TL	18.4R42	03395	73.1	33.4	218.2	309	69	13,200	41
520/85R42 TL 157A8/157B	20.8R42	63687	76.6	34.2	227.2	469	74	13,530	27
420/80R46 TL 151A8/148B	16.9R46	58733	73.7	33.9	218.7	274	64	11,330	41
480/80R46 TL 158A8/155B	18.4R46	94069	76.7	35.0	231.3	357	68	14,036	41
520/85R46 TL 158A8/155B	20.8R46	57479	80.7	36.2	239.7	496	73	14,036	27
480/80R50 TL 159A8/159B		94576	80.9	37.1	243.5	360	71	14,300	41

Machine Types



2WD Tractors



4WD Tractors



MFWA Tractors



Sprayers



Harvesters



Trailers