



CargoXbib® radial stands up to any comparison in terms of rolling resistance, load capacity and soil protection, with all the attributes of a high performance radial casing.

#### Ultra Low Soil Compaction

The CargoXbib® carries high loads at lower pressures. With its large contact patch and rounded shoulders, the tire offers maximum flotation, minimizing rutting and soil damage.

#### Exceptionally Low Rolling Resistance

The exceptionally low rolling resistance greatly reduces the tractive force required to pull trailers equipped with CargoXbib® (40% less compared to bias-ply), resulting in increased productivity and fuel savings.

#### Impressive Load Carrying Capacity at High Speed

Radial casing and reinforced construction give extraordinary load capacity at speeds up to 40 mph (65 km/h).

#### Exceptional Stability and Comfort

The CargoXbib® with its tread blocks helps improve the stability of equipment in the raised position. The tread blocks also contribute to excellent handling on sidehill slopes by providing an effective support base. Radial casing technology and low pressures provide a soft smooth ride.

## English Units

CargoXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in <sup>2</sup> )	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
500/60R22.5 TL 155D		73552	46.5	20.4	137.2	243	21	15,356	58
560/60R22.5 TL 161D		75840	49.3	21.1	144.8	288	21	18,326	58
600/50R22.5 TL 159D		94336	46.5	20.1	136.9	285	21	17,336	58
710/45R22.5 TL 165D		49366	47.6	20.3	139.8	336	21	20,394	58
600/55R26.5 TL 165D		42913	53.1	23.1	156.5	331	24	20,394	58

CargoXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in <sup>2</sup> )	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
710/50R26.5 TL 170D		77969	55.3	23.9	162.8	408	24	23,760	58
800/45R26.5 TL 174D		81371	54.9	23.4	161.3	421	24	26,532	58
600/60R30.5 TL 169D		51915	58.9	25.7	173.9	376	26	22,968	58
650/65R30.5 TL 176D		94604	63.9	27.5	188.0	445	28	28,116	58
710/50R30.5 TL 173D		92209	58.9	25.6	173.5	420	26	25,740	58
750/60R30.5 TL 181D		83575	66.1	28.3	194.3	538	29	32,670	58
800/45R30.5 TL 176D		53255	58.9	25.6	173.5	462	26	28,116	58
850/50R30.5 TL 182D		69986	64.1	27.2	188.1	555	29	33,660	58

## Machine Types



**Floaters**



**Trailers**