

Soil Protection is #1

- Carrying heavy loads at ultra-low pressures with a huge soft footprint and rounded shoulders, the MACHXBIB® helps deliver vital soil protection during preparation, planting and treatment. Rutting is minimized.
- A flat stable tread spreads the load evenly across the footprint, helping to minimize soil compaction by providing excellent ground pressure distribution.

High Load Capacity

A large air chamber, stabilized tread and reinforced radial casing allow the MACHXBIB® to carry heavy loads at low pressures.

Extraordinary Traction and Efficiency

A broad flat crown with long deep lugs give the MACHXBIB® a low slip rate and minimal rolling resistance, giving more traction, and resulting in time & fuel savings.

Exceptional Comfort and Handling

- The swept-back 45° lug design delivers an exceptionally smooth ride on the road at speeds of up to 30 mph.
- An ultra-flexible but super-strong casing and low air pressures deliver sensational ride comfort in the field and on the road.



English Units

MachXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
600/65R28 TL 154A8/154B		86350	58.9	26.3	174.6	341	64	12,386	35
600/70R28 TL 157A8/157B		46139	62.1	27.7	185.2	378	67	13,618	35
600/70R30 TL 152A8/152B		68024	63.0	27.9	186.5	369	71	11,726	27
710/55R30 TL 153A8/153B		73905	59.7	26.5	176.8	387	63	12,056	27
650/75R38 TL 169A8/169B		86829	76.7	34.6	226.8	510	77	19,140	41

MachXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
650/85R38 TL 173A8/173B		89462	81.2	36.4	239.8	583	81	21,450	41
710/70R38 171A8/171B TL		35929	77.0	34.0	226.1	0	76	20,306	41
800/70R38 TL 173A8/173B		72379	81.6	35.5	240.7	720	77	21,450	27
620/70R42 166A8/166B TL		24383	76.9	34.7	228.7	447	71	17,490	41
710/70R42 173A8/173B TL		36718	80.7	36.2	239.7	0	77	83,270	41
900/50R42 TL 168A8/168B		71498	76.7	33.9	228.9	717	72	18,700	27

Machine Types



4WD Tractors



MFWA Tractors