



Ultra-Low Soil Compaction

The MEGAXBIB® is an excellent choice for situations where flotation and reduced compaction are critical.

Impressive Load Carrying Capacity

A huge footprint and extra-large air chamber combined with a special casing design allow the MEGAXBIB® to carry extremely heavy loads at relatively low pressures.

Broad Flat Footprint - Excellent Ground Pressure Distribution

A flat stable tread spreads the load evenly across the footprint, helping to maximize flotation and minimize soil compaction.

Exceptional Comfort

Ultra-low pressures and super-flexible sidewalls give the MEGAXBIB® a soft comfortable ride, with surprising stability and handling on the road.

English Units

MegaXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
1000/50R25 (66x43.00-25) 172A8/166D TL MEGAXBIB T1		83399	64.8	28.4	194.2	643	58	13,860	35
750/50R26 157A8/151D TL MEGAXBIB		15686	55.3	24.4	163.7	0	48	9,075	35
580/70R26 TL 149A8/146B		49571	56.5	24.8	169.3	539	55	7,150	23
620/75R26 TL 166A8/166B	23.1R26	89936	63.1	28.0	186.9	395	58	11,660	46
620/70R26 TL 153A8/150B		53054	59.1	25.3	175.9	412	57	8,030	23
750/65R26 TL 166A8/166B	28LR26	91020	63.8	28.5	189.4	432	58	11,660	35
620/75R30 TL 168A8/168B	23.1R30	63928	67.3	30.3	200.1	422	58	12,320	46

MegaXbib Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
1050/50R32 (73x44.00-32) 178A8/172D TL MEGAXBIB T2		04644	73.1	32.4	216.7	730	52	16,500	35
650/75R32 TL 172A8/172B	24.5R32	46686	71.9	32.3	213.5	465	74	13,860	46
800/65R32 TL 172A8/172B	30.5LR32	79035	72.4	32.4	214.9	571	71	13,860	35
900/60R32 TL 176A8/176B	35.5R32	59226	74.6	33.2	221.0	662	71	15,620	35
1050/50R32 TL 178A8 M28	73x44.00-32 18PR	94737	74.9	33.6	222.4	745	76	16,500	35
620/75R34 TL 170A8/170B	23.1R34	83734	71.4	32.3	212.5	450	58	13,200	46
620/70R38 TL 170A8/170B		99512	73.4	33.5	218.8	451	69	13,200	46



MFWA Tractors



Harvesters



Floaters