



**Excellent Flotation and Traction**

With its wide flat tread and R1W deep lugs the XM28™ provides excellent flotation, traction and mobility in adverse field conditions.

**Extraordinary Productivity**

Low slip rate and minimal rolling resistance delivered by the XM28™ result in extraordinary time and fuel savings.

**Low Soil Compaction**

A super-flat tread spreads the load evenly across an oversize footprint, reducing the tire's penetration into soft soil. Decreased slip and ultra-low working pressures help to reduce soil compaction and damage.

**Exceptional Comfort**

Uniform "round" construction plus Michelin's super-strong but ultra-flexible casing deliver exceptional ride and comfort, in the field and on the road.

**English Units**

XM28 Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in <sup>2</sup> )	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
710/70R42 173A8/173B TL XM28		98355	80.9	36.6	240.8	505	73	21,450	39
600/65R28 TL 147A8/147B		88859	58.7	26.1	173.8	352	58	10,142	27
650/75R32 TL 159A8/156B	24.5R32	77317	71.7	31.1	211.3	494	73	14,432	27
680/75R32 TL 164A8/161B		80305	73.4	31.9	215.6	545	73	16,500	27
710/70R38 TL 166A8/166B		50825	76.7	33.7	226.6	524	71	17,490	27
620/70R46 TL 162A8/162B		69879	81.1	36.5	241.0	498	72	15,686	27

## Machine Types



**4WD Tractors**



**MFWD Tractors**



**Harvesters**



**Sprayers**



**Trailers**