

XMCL™ UTILITY & INDUSTRIAL

Designed for Use in a Variety of Utility and Industrial Applications Michelin's most versatile drive tire for Compact Line Equipment including Backhoes, Telescopic Handlers and Utility Tractor Applications.

Outstanding Puncture And Damage Resistance

Tire construction features a steel crown belt package for extra protection.

Extremely Long Tire Life

Massive lugs designed for optimized wear offer increased service life versus our XM27™ radial.

Extraordinary Traction

Radial technology, an aggressive tread pattern and a flat stable crown help give extraordinary traction in all kinds of job conditions.

High Load Capacity

With a casing designed for extra load capacity, the XMCL™ tire helps provide up to 50% greater carrying capacity than the XM27™ tire.



English Units

XMCL Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
280/80R18 (275/80R18) 132A8/132B IND TL XMCL		25391	35.7	16.3	106.6	101	35	10,120	64
280/80R20 (275/80R20) (10.5R20) 133A8/133B IND TL XMCL		32621	37.7	17.3	112.6	108	37	10,428	64
340/80R18 (335/80R18) (12.5R18) 143A8/143B IND TL XMCL		24643	39.2	17.6	116.5	135	38	13,794	64
340/80R20 (335/80R20) (12.5R20) 144A8/144B IND TL XMCL		00733	41.2	18.7	122.8	143	37	14,168	64
380/75R20 (375/75R20) 148A8/148B IND TL XMCL		03424	42.1	18.9	125.9	169	42	15,950	64
400/70R20 (405/70R20) (14.5R20) 149A8/149B IND TL XMCL		02871	42.1	18.9	125.1	184	42	16,456	64
420/75R20 (425/75R20) 154A8/154B IND TL XMCL		19152	44.8	20.0	133.0	196	42	18,986	64

XMCL Sizes	Equiv. Size	MSPN	Overall Diameter (in)	Loaded Radius (in)	Rolling Circumference (in)	Gross Flat Plate (in ²)	Center-line Tread Depth (32nd")	Max Load @ 25mph (lbs)	Max Pressure @ 25 mph (psi)
440/80R24 (16.9R24) 161A8/161B IND TL XMCL		34933	51.7	23.3	153.8	262	45	23,408	64
440/80R28 (16.9R28) 156A8/156B IND TL XMCL		94482	55.5	25.2	165.4	254	45	20,240	52
460/70R24 (17.5LR24) (440/70R24) 159A8/159B IND TL XMCL		70333	49.1	22.1	146.0	230	45	22,132	64
480/80R26 (18.4R26) 160A8/160B IND TL XMCL		16032	56.0	25.0	166.1	282	45	22,770	52
500/70R24 (19.5LR24) 164A8/164B IND TL XMCL		89582	51.3	23.0	152.2	280	45	25,300	64

Machine Types



Telescopic Handlers



Backhoes



Skid Steer Loader